

# NWERC 2023

Solutions presentation

---

The NWERC 2023 jury

November 26, 2023

## The NWERC 2023 Jury

- **Doan-Dai Nguyen**  
École normale supérieure -  
Université Paris Sciences & Lettres
- **Jeroen Bransen**  
Chordify
- **Maarten Sijm**  
CHipCie (Delft University of Technology)
- **Michael Zündorf**  
Karlsruhe Institute of Technology
- **Nils Gustafsson**  
KTH Royal Institute of Technology
- **Paul Wild**  
FAU Erlangen-Nürnberg
- **Ragnar Groot Koerkamp**  
ETH Zurich
- **Reinier Schmiermann**  
Utrecht University
- **Wendy Yi**  
Karlsruhe Institute of Technology

## Big thanks to our proofreaders and test solvers

- **Dany Sluijk**  
Delft University of Technology
- **Mees de Vries**  
BAPC Jury
- **Oleksandr Kulkov**  
ETH Zurich
- **Pavel Kunyavskiy**  
JetBrains, Amsterdam
- **Robin Lee**  
Google
- **Vitaly Aksenov**  
City, University of London

# A: Arranging Adapters

Problem Author: Michael Zündorf

## Problem

Given  $1 \leq n \leq 2 \cdot 10^5$  chargers, each  $3 \leq w \leq 10^9$  cm wide, how many fit into a powerstrip comprising a row of  $1 \leq s \leq 10^5$  sockets, each of width 3 cm?

# A: Arranging Adapters

Problem Author: Michael Zündorf

## Problem

Given  $1 \leq n \leq 2 \cdot 10^5$  chargers, each  $3 \leq w \leq 10^9$  cm wide, how many fit into a powerstrip comprising a row of  $1 \leq s \leq 10^5$  sockets, each of width 3 cm?

## Solution

- First, greedily put the two largest chargers on the outside.

# A: Arranging Adapters

Problem Author: Michael Zündorf

## Problem

Given  $1 \leq n \leq 2 \cdot 10^5$  chargers, each  $3 \leq w \leq 10^9$  cm wide, how many fit into a powerstrip comprising a row of  $1 \leq s \leq 10^5$  sockets, each of width 3 cm?

## Solution

- First, greedily put the two largest chargers on the outside.
- If the answer is  $k$ , we can use the  $k$  smallest chargers.

# A: Arranging Adapters

Problem Author: Michael Zündorf

## Problem

Given  $1 \leq n \leq 2 \cdot 10^5$  chargers, each  $3 \leq w \leq 10^9$  cm wide, how many fit into a powerstrip comprising a row of  $1 \leq s \leq 10^5$  sockets, each of width 3 cm?

## Solution

- First, greedily put the two largest chargers on the outside.
- If the answer is  $k$ , we can use the  $k$  smallest chargers.
- To test if the smallest  $k$  chargers fit:
  - Start with those of length  $0 \pmod 3$ .
  - Then pair up  $1 \pmod 3$  and  $2 \pmod 3$  chargers, filling the gaps.
  - Then pair up remaining  $1 \pmod 3$ , leaving a gap of 1 in between.
  - Lastly put the remaining chargers, and check the total length used.

# A: Arranging Adapters

Problem Author: Michael Zündorf

## Problem

Given  $1 \leq n \leq 2 \cdot 10^5$  chargers, each  $3 \leq w \leq 10^9$  cm wide, how many fit into a powerstrip comprising a row of  $1 \leq s \leq 10^5$  sockets, each of width 3 cm?

## Solution

- First, greedily put the two largest chargers on the outside.
- If the answer is  $k$ , we can use the  $k$  smallest chargers.
- To test if the smallest  $k$  chargers fit:
  - Start with those of length  $0 \pmod 3$ .
  - Then pair up  $1 \pmod 3$  and  $2 \pmod 3$  chargers, filling the gaps.
  - Then pair up remaining  $1 \pmod 3$ , leaving a gap of 1 in between.
  - Lastly put the remaining chargers, and check the total length used.
- Binary search over  $k$ . Runtime  $\mathcal{O}(n \log n)$ .

# A: Arranging Adapters

Problem Author: Michael Zündorf

## Problem

Given  $1 \leq n \leq 2 \cdot 10^5$  chargers, each  $3 \leq w \leq 10^9$  cm wide, how many fit into a powerstrip comprising a row of  $1 \leq s \leq 10^5$  sockets, each of width 3 cm?

## Solution

- First, greedily put the two largest chargers on the outside.
- If the answer is  $k$ , we can use the  $k$  smallest chargers.
- To test if the smallest  $k$  chargers fit:
  - Start with those of length  $0 \pmod 3$ .
  - Then pair up  $1 \pmod 3$  and  $2 \pmod 3$  chargers, filling the gaps.
  - Then pair up remaining  $1 \pmod 3$ , leaving a gap of 1 in between.
  - Lastly put the remaining chargers, and check the total length used.
- Binary search over  $k$ . Runtime  $\mathcal{O}(n \log n)$ .
- Edge case: when there is only a single socket.

# A: Arranging Adapters

Problem Author: Michael Zündorf

## Problem

Given  $1 \leq n \leq 2 \cdot 10^5$  chargers, each  $3 \leq w \leq 10^9$  cm wide, how many fit into a powerstrip comprising a row of  $1 \leq s \leq 10^5$  sockets, each of width 3 cm?

## Solution

- First, greedily put the two largest chargers on the outside.
- If the answer is  $k$ , we can use the  $k$  smallest chargers.
- To test if the smallest  $k$  chargers fit:
  - Start with those of length  $0 \pmod 3$ .
  - Then pair up  $1 \pmod 3$  and  $2 \pmod 3$  chargers, filling the gaps.
  - Then pair up remaining  $1 \pmod 3$ , leaving a gap of 1 in between.
  - Lastly put the remaining chargers, and check the total length used.
- Binary search over  $k$ . Runtime  $\mathcal{O}(n \log n)$ .
- Edge case: when there is only a single socket.
- Linear time is also possible, trying to add one charger at a time.

# A: Arranging Adapters

Problem Author: Michael Zündorf

## Problem

Given  $1 \leq n \leq 2 \cdot 10^5$  chargers, each  $3 \leq w \leq 10^9$  cm wide, how many fit into a powerstrip comprising a row of  $1 \leq s \leq 10^5$  sockets, each of width 3 cm?

## Solution

- First, greedily put the two largest chargers on the outside.
- If the answer is  $k$ , we can use the  $k$  smallest chargers.
- To test if the smallest  $k$  chargers fit:
  - Start with those of length  $0 \pmod 3$ .
  - Then pair up  $1 \pmod 3$  and  $2 \pmod 3$  chargers, filling the gaps.
  - Then pair up remaining  $1 \pmod 3$ , leaving a gap of 1 in between.
  - Lastly put the remaining chargers, and check the total length used.
- Binary search over  $k$ . Runtime  $\mathcal{O}(n \log n)$ .
- Edge case: when there is only a single socket.
- Linear time is also possible, trying to add one charger at a time.

# A: Arranging Adapters

Problem Author: Michael Zündorf

## Problem

Given  $1 \leq n \leq 2 \cdot 10^5$  chargers, each  $3 \leq w \leq 10^9$  cm wide, how many fit into a powerstrip comprising a row of  $1 \leq s \leq 10^5$  sockets, each of width 3 cm?

## Solution

- First, greedily put the two largest chargers on the outside.
- If the answer is  $k$ , we can use the  $k$  smallest chargers.
- To test if the smallest  $k$  chargers fit:
  - Start with those of length  $0 \pmod 3$ .
  - Then pair up  $1 \pmod 3$  and  $2 \pmod 3$  chargers, filling the gaps.
  - Then pair up remaining  $1 \pmod 3$ , leaving a gap of 1 in between.
  - Lastly put the remaining chargers, and check the total length used.
- Binary search over  $k$ . Runtime  $\mathcal{O}(n \log n)$ .
- Edge case: when there is only a single socket.
- Linear time is also possible, trying to add one charger at a time.

Statistics: ... submissions, ... accepted, ... unknown

# B: Brickwork

Problem Author: Michael Zündorf

## Problem

Given  $n$  types of bricks  $b_1, \dots, b_n$ , can you build a wall of width  $w$  where no two gaps appear above each other?



# B: Brickwork

Problem Author: Michael Zündorf

## Subtask

Can at least one row be built?

# B: Brickwork

Problem Author: Michael Zündorf

## Subtask

Can at least one row be built?

## Solution

This is known as the *coin change problem* and can be solved like this:

- $\mathcal{O}\left(\frac{w^2}{64}\right)$  with dp + bitsets
- $\mathcal{O}(w \log(w)^2)$  with fft (faster is possible)

# B: Brickwork

Problem Author: Michael Zündorf

## Subtask

Can at least one row be built?

## Solution

This is known as the *coin change problem* and can be solved like this:

- $\mathcal{O}\left(\frac{w^2}{64}\right)$  with dp + bitsets
- $\mathcal{O}(w \log(w)^2)$  with fft (faster is possible)
- Bitsets are much faster

# B: Brickwork

Problem Author: Michael Zündorf

## Case 1

- $w \in \{b_1, \dots, b_n\}$



# B: Brickwork

Problem Author: Michael Zündorf

## Case 1

- $w \in \{b_1, \dots, b_n\}$



## Case 2

- There is a row that uses two bricks  $b_x, b_y$

# B: Brickwork

Problem Author: Michael Zündorf

## Case 1

- $w \in \{b_1, \dots, b_n\}$



## Case 2

- There is a row that uses two bricks  $b_x, b_y$
- WLOG:
  - Let  $b_x$  be the shortest
  - Let  $b_y$  be the second shortest
  - there are as few  $b_x$  as possible  
(still at least one)

# B: Brickwork

Problem Author: Michael Zündorf

## Case 1

- $w \in \{b_1, \dots, b_n\}$



## Case 2

- There is a row that uses two bricks  $b_x, b_y$
- WLOG:
  - Let  $b_x$  be the shortest
  - Let  $b_y$  be the second shortest
  - there are as few  $b_x$  as possible (still at least one)

## Case 2.1

- Sum of  $b_x$  can be replaced by some  $b_y$



# B: Brickwork

Problem Author: Michael Zündorf

## Case 1

- $w \in \{b_1, \dots, b_n\}$



## Case 2

- There is a row that uses two bricks  $b_x, b_y$
- WLOG:
  - Let  $b_x$  be the shortest
  - Let  $b_y$  be the second shortest
  - there are as few  $b_x$  as possible (still at least one)

## Case 2.1

- Sum of  $b_x$  can be replaced by some  $b_y$



## Case 2.2

- Else



# B: Brickwork

Problem Author: Michael Zündorf

## Case 3


- There are two bricks  $b_x, b_y$  that divide  $w$

# B: Brickwork

Problem Author: Michael Zündorf

## Case 3

- There are two bricks  $b_x, b_y$  that divide  $w$
- Case 2 implies that  $lcm(b_x, b_y) = w$




# B: Brickwork

Problem Author: Michael Zündorf

## Case 3

- There are two bricks  $b_x, b_y$  that divide  $w$
- Case 2 implies that  $lcm(b_x, b_y) = w$



## Case 4

- Impossible

## Conclusion

The solution exists in two cases:


- Trivial:  $w \in \{b_1, \dots, b_n\}$
- There exist two bricks that both can be part of a solution

# B: Brickwork

Problem Author: Michael Zündorf

## Case 3

- There are two bricks  $b_x, b_y$  that divide  $w$
- Case 2 implies that  $lcm(b_x, b_y) = w$



## Case 4

- Impossible

## Conclusion

The solution exists in two cases:

- Trivial:  $w \in \{b_1, \dots, b_n\}$
- There exist two bricks that both can be part of a solution

Statistics: ... submissions, ... accepted, ... unknown

# C: Chair Dance

Problem Author: Michael Zündorf

## Problem

Given are  $n \leq 10^5$  players playing a deterministic version of *musical chairs*. Player  $i$  starts on chair  $i$ . Apply up to  $10^5$  commands:

- Rotate by  $+r$ : the person on chair  $i$  moves clockwise to chair  $i + r$ .
- Multiply by  $*m$ , the person on chair  $i$  moves to  $i \cdot m$ , where the person walking the least gets it.
- On  $?q$ , print who sits on chair  $q$ .

# C: Chair Dance

Problem Author: Michael Zündorf

## Problem

Given are  $n \leq 10^5$  players playing a deterministic version of *musical chairs*. Player  $i$  starts on chair  $i$ . Apply up to  $10^5$  commands:

- Rotate by  $+r$ : the person on chair  $i$  moves clockwise to chair  $i + r$ .
- Multiply by  $*m$ , the person on chair  $i$  moves to  $i \cdot m$ , where the person walking the least gets it.
- On  $?q$ , print who sits on chair  $q$ .

## Naive solution

Store who sits on each chair, and apply each command.  $\mathcal{O}(n^2)$

# C: Chair Dance

Problem Author: Michael Zündorf

## Solution

Be *lazy*! Initialize  $p[i] = i$ , the person on chair  $i$ .

- Instead of rotating by  $+r$ , increment the *total rotation*  $R$ .  $p[i]$  is now at  $i + R$ , so query  $p[q - R]$ .

# C: Chair Dance

Problem Author: Michael Zündorf

## Solution

Be *lazy*! Initialize  $p[i] = i$ , the person on chair  $i$ .

- Instead of rotating by  $+r$ , increment the *total rotation*  $R$ .  $p[i]$  is now at  $i + R$ , so query  $p[q - R]$ .
- For *collision-free* multiplications: store total multiplication  $M$ , so  $p[i]$  is now at  $M \cdot i + R$ . When multiplying by  $m$ , update  $M \leftarrow m \cdot M$  and  $R \leftarrow m \cdot R$ . Query  $p[(q - R) \cdot M^{-1}]$ .

# C: Chair Dance

Problem Author: Michael Zündorf

## Solution

Be *lazy*! Initialize  $p[i] = i$ , the person on chair  $i$ .

- Instead of rotating by  $+r$ , increment the *total rotation*  $R$ .  $p[i]$  is now at  $i + R$ , so query  $p[q - R]$ .
- For *collision-free* multiplications: store total multiplication  $M$ , so  $p[i]$  is now at  $M \cdot i + R$ . When multiplying by  $m$ , update  $M \leftarrow m \cdot M$  and  $R \leftarrow m \cdot R$ . Query  $p[(q - R) \cdot M^{-1}]$ .
- Collisions occur when  $\gcd(m, k) > 1$  ( $k = \#$ leftover people). Simulate these fully, set  $k \leftarrow k / \gcd(m, k)$ , and reset  $R$  and  $M$ .

# C: Chair Dance

Problem Author: Michael Zündorf

## Solution

Be *lazy*! Initialize  $p[i] = i$ , the person on chair  $i$ .

- Instead of rotating by  $+r$ , increment the *total rotation*  $R$ .  $p[i]$  is now at  $i + R$ , so query  $p[q - R]$ .
- For *collision-free* multiplications: store total multiplication  $M$ , so  $p[i]$  is now at  $M \cdot i + R$ . When multiplying by  $m$ , update  $M \leftarrow m \cdot M$  and  $R \leftarrow m \cdot R$ . Query  $p[(q - R) \cdot M^{-1}]$ .
- Collisions occur when  $\gcd(m, k) > 1$  ( $k = \#$ leftover people). Simulate these fully, set  $k \leftarrow k / \gcd(m, k)$ , and reset  $R$  and  $M$ .
- Be careful about queries to empty chairs.

# C: Chair Dance

Problem Author: Michael Züendorf

## Solution

Be *lazy*! Initialize  $p[i] = i$ , the person on chair  $i$ .

- Instead of rotating by  $+r$ , increment the *total rotation*  $R$ .  $p[i]$  is now at  $i + R$ , so query  $p[q - R]$ .
- For *collision-free* multiplications: store total multiplication  $M$ , so  $p[i]$  is now at  $M \cdot i + R$ . When multiplying by  $m$ , update  $M \leftarrow m \cdot M$  and  $R \leftarrow m \cdot R$ . Query  $p[(q - R) \cdot M^{-1}]$ .
- Collisions occur when  $\gcd(m, k) > 1$  ( $k = \#$ leftover people). Simulate these fully, set  $k \leftarrow k / \gcd(m, k)$ , and reset  $R$  and  $M$ .
- Be careful about queries to empty chairs.
- Each collision at least halves  $k$ , so at most  $\lg n$  collisions.

# C: Chair Dance

Problem Author: Michael Zündorf

## Solution

Be *lazy*! Initialize  $p[i] = i$ , the person on chair  $i$ .

- Instead of rotating by  $+r$ , increment the *total rotation*  $R$ .  $p[i]$  is now at  $i + R$ , so query  $p[q - R]$ .
- For *collision-free* multiplications: store total multiplication  $M$ , so  $p[i]$  is now at  $M \cdot i + R$ . When multiplying by  $m$ , update  $M \leftarrow m \cdot M$  and  $R \leftarrow m \cdot R$ . Query  $p[(q - R) \cdot M^{-1}]$ .
- Collisions occur when  $\gcd(m, k) > 1$  ( $k = \#$ leftover people). Simulate these fully, set  $k \leftarrow k / \gcd(m, k)$ , and reset  $R$  and  $M$ .
- Be careful about queries to empty chairs.
- Each collision at least halves  $k$ , so at most  $\lg n$  collisions.
- Runtime:  $\mathcal{O}(n \log n)$ .

## C: Chair Dance

Problem Author: Michael Zündorf

### Solution

Be *lazy*! Initialize  $p[i] = i$ , the person on chair  $i$ .

- Instead of rotating by  $+r$ , increment the *total rotation*  $R$ .  $p[i]$  is now at  $i + R$ , so query  $p[q - R]$ .
- For *collision-free* multiplications: store total multiplication  $M$ , so  $p[i]$  is now at  $M \cdot i + R$ . When multiplying by  $m$ , update  $M \leftarrow m \cdot M$  and  $R \leftarrow m \cdot R$ . Query  $p[(q - R) \cdot M^{-1}]$ .
- Collisions occur when  $\gcd(m, k) > 1$  ( $k = \#$ leftover people). Simulate these fully, set  $k \leftarrow k / \gcd(m, k)$ , and reset  $R$  and  $M$ .
- Be careful about queries to empty chairs.
- Each collision at least halves  $k$ , so at most  $\lg n$  collisions.
- Runtime:  $\mathcal{O}(n \log n)$ .

Statistics: ... submissions, ... accepted, ... unknown

# D: Date Picker

Problem Author: Jeroen Bransen

## Problem

Given your availability for every hour in a week, pick at least  $1 \leq d \leq 7$  days in the first poll and at least  $1 \leq h \leq 24$  hours in the second poll to get the highest probability that you will be available.

Fun fact: based on a true story, while the jury was planning their first meeting!

# D: Date Picker

Problem Author: Jeroen Bransen

## Problem

Given your availability for every hour in a week, pick at least  $1 \leq d \leq 7$  days in the first poll and at least  $1 \leq h \leq 24$  hours in the second poll to get the highest probability that you will be available.

Fun fact: based on a true story, while the jury was planning their first meeting!

## Observation

Selecting more than  $d$  days/ $h$  hours is never more efficient than selecting exactly  $d$  days/ $h$  hours.

# D: Date Picker

Problem Author: Jeroen Bransen

## Problem

Given your availability for every hour in a week, pick at least  $1 \leq d \leq 7$  days in the first poll and at least  $1 \leq h \leq 24$  hours in the second poll to get the highest probability that you will be available.

Fun fact: based on a true story, while the jury was planning their first meeting!

## Observation

Selecting more than  $d$  days/ $h$  hours is never more efficient than selecting exactly  $d$  days/ $h$  hours.

## Brute-force solution

For every combination of (a subset of  $d$  days) and (a subset of  $h$  hours), calculate the number of free timeslots, take the maximum, and divide by  $d \cdot h$ .

# D: Date Picker

Problem Author: Jeroen Bransen

## Problem

Given your availability for every hour in a week, pick at least  $1 \leq d \leq 7$  days in the first poll and at least  $1 \leq h \leq 24$  hours in the second poll to get the highest probability that you will be available.

Fun fact: based on a true story, while the jury was planning their first meeting!

## Observation

Selecting more than  $d$  days/ $h$  hours is never more efficient than selecting exactly  $d$  days/ $h$  hours.

## Brute-force solution

For every combination of (a subset of  $d$  days) and (a subset of  $h$  hours), calculate the number of free timeslots, take the maximum, and divide by  $d \cdot h$ . **Too slow:** in the worst case where  $d = 3$  and  $h = 12$ , this requires checking  $\binom{7}{3} \cdot \binom{24}{12} \cdot 3 \cdot 12 \approx 3 \cdot 10^9$  timeslots.

# D: Date Picker

Problem Author: Jeroen Bransen

## Problem

Given your availability for every hour in a week, pick at least  $1 \leq d \leq 7$  days in the first poll and at least  $1 \leq h \leq 24$  hours in the second poll to get the highest probability that you will be available.

Fun fact: based on a true story, while the jury was planning their first meeting!

## Observation

Selecting more than  $d$  days/ $h$  hours is never more efficient than selecting exactly  $d$  days/ $h$  hours.

## Brute-force solution

For every combination of (a subset of  $d$  days) and (a subset of  $h$  hours), calculate the number of free timeslots, take the maximum, and divide by  $d \cdot h$ . **Too slow:** in the worst case where  $d = 3$  and  $h = 12$ , this requires checking  $\binom{7}{3} \cdot \binom{24}{12} \cdot 3 \cdot 12 \approx 3 \cdot 10^9$  timeslots. (Unless you write *very* efficient C++)

# D: Date Picker

Problem Author: Jeroen Bransen

## Problem

Given your availability for every hour in a week, pick at least  $1 \leq d \leq 7$  days in the first poll and at least  $1 \leq h \leq 24$  hours in the second poll to get the highest probability that you will be available.

Fun fact: based on a true story, while the jury was planning their first meeting!

## Greedy Solution

To avoid having to check all combinations, only check all combinations of  $d$  days.

# D: Date Picker

Problem Author: Jeroen Bransen

## Problem

Given your availability for every hour in a week, pick at least  $1 \leq d \leq 7$  days in the first poll and at least  $1 \leq h \leq 24$  hours in the second poll to get the highest probability that you will be available.

Fun fact: based on a true story, while the jury was planning their first meeting!

## Greedy Solution

To avoid having to check all combinations, only check all combinations of  $d$  days.

For every combination of  $d$  days:

- For every hour, count the number of cells with '.'.
- Sort this list and select the  $h$  hours with the most open timeslots.
- Calculate the number of free timeslots, take the maximum, and divide by  $d \cdot h$ .

# D: Date Picker

Problem Author: Jeroen Bransen

## Problem

Given your availability for every hour in a week, pick at least  $1 \leq d \leq 7$  days in the first poll and at least  $1 \leq h \leq 24$  hours in the second poll to get the highest probability that you will be available.

Fun fact: based on a true story, while the jury was planning their first meeting!

## Greedy Solution

To avoid having to check all combinations, only check all combinations of  $d$  days.

For every combination of  $d$  days:

- For every hour, count the number of cells with '.'.
- Sort this list and select the  $h$  hours with the most open timeslots.
- Calculate the number of free timeslots, take the maximum, and divide by  $d \cdot h$ .

Statistics: ... submissions, ... accepted, ... unknown

# E: Exponentiation

Problem Author: Reinier Schmiermann

## Problem

There are  $n$  variables  $x_1, x_2, \dots, x_n$ , initially set to 2023. You are given  $m$  queries that either assigns  $x_i$  to  $x_i^{x_j}$ , or asks you to compare  $x_i$  and  $x_j$ .

## Observation

- To make the numbers slightly less huge, take the logarithm twice. Let  $y_i = \log \log(x_i)$ .

# E: Exponentiation

Problem Author: Reinier Schmiermann

## Problem

There are  $n$  variables  $x_1, x_2, \dots, x_n$ , initially set to 2023. You are given  $m$  queries that either assigns  $x_i$  to  $x_i^{x_j}$ , or asks you to compare  $x_i$  and  $x_j$ .

## Observation

- To make the numbers slightly less huge, take the logarithm twice. Let  $y_i = \log \log(x_i)$ .
- $x_i = x_i^{x_j} \equiv y_i = y_i + 2023^{y_j}$ .

# E: Exponentiation

Problem Author: Reinier Schmiermann

## Problem

There are  $n$  variables  $x_1, x_2, \dots, x_n$ , initially set to 2023. You are given  $m$  queries that either assigns  $x_i$  to  $x_i^{x_j}$ , or asks you to compare  $x_i$  and  $x_j$ .

## Observation

- To make the numbers slightly less huge, take the logarithm twice. Let  $y_i = \log \log(x_i)$ .
- $x_i = x_i^{x_j} \equiv y_i = y_i + 2023^{y_j}$ .
- Consider these numbers in base 2023. Each operation, one of the digits will increase by one. But no carry will ever happen since there are fewer than 2023 operations.

# E: Exponentiation

Problem Author: Reinier Schmiermann

## Solution

- Represent every variable as a list containing the positions of its non-zero digits. Two such numbers can be compared by lexicographically comparing their lists.

# E: Exponentiation

Problem Author: Reinier Schmiermann

## Solution

- Represent every variable as a list containing the positions of its non-zero digits. Two such numbers can be compared by lexicographically comparing their lists.
- When a variable gets updated, it is much easier to create a new variable  $y' = y_i + 2023^{y_j}$ .

# E: Exponentiation

Problem Author: Reinier Schmiermann

## Solution

- Represent every variable as a list containing the positions of its non-zero digits. Two such numbers can be compared by lexicographically comparing their lists.
- When a variable gets updated, it is much easier to create a new variable  $y' = y_i + 2023^{y_j}$ .
- Order the variables by size at all times. When a new variable  $y'$  is created, copy the list of  $y_i$  and add  $y_j$  to it. Sort the list of  $y'$  and insert it into the order.

# E: Exponentiation

Problem Author: Reinier Schmiermann

## Solution

- Represent every variable as a list containing the positions of its non-zero digits. Two such numbers can be compared by lexicographically comparing their lists.
- When a variable gets updated, it is much easier to create a new variable  $y' = y_i + 2023^{y_j}$ .
- Order the variables by size at all times. When a new variable  $y'$  is created, copy the list of  $y_i$  and add  $y_j$  to it. Sort the list of  $y'$  and insert it into the order.
- The ordering can be a trie, or just an array. This can be done in  $\mathcal{O}(n^2)$  or  $\mathcal{O}(n^2 \log(n))$ .

# E: Exponentiation

Problem Author: Reinier Schmiermann

## Solution

- Represent every variable as a list containing the positions of its non-zero digits. Two such numbers can be compared by lexicographically comparing their lists.
- When a variable gets updated, it is much easier to create a new variable  $y' = y_i + 2023^{y_j}$ .
- Order the variables by size at all times. When a new variable  $y'$  is created, copy the list of  $y_i$  and add  $y_j$  to it. Sort the list of  $y'$  and insert it into the order.
- The ordering can be a trie, or just an array. This can be done in  $\mathcal{O}(n^2)$  or  $\mathcal{O}(n^2 \log(n))$ .
- **Challenge:** can you solve the problem faster than quadratic time?

# E: Exponentiation

Problem Author: Reinier Schmiermann

## Solution

- Represent every variable as a list containing the positions of its non-zero digits. Two such numbers can be compared by lexicographically comparing their lists.
- When a variable gets updated, it is much easier to create a new variable  $y' = y_i + 2023^{y_j}$ .
- Order the variables by size at all times. When a new variable  $y'$  is created, copy the list of  $y_i$  and add  $y_j$  to it. Sort the list of  $y'$  and insert it into the order.
- The ordering can be a trie, or just an array. This can be done in  $\mathcal{O}(n^2)$  or  $\mathcal{O}(n^2 \log(n))$ .
- **Challenge:** can you solve the problem faster than quadratic time?

Statistics: ... submissions, ... accepted, ... unknown

# F: Fixing Fractions

Problem Author: Michael Zündorf

## Problem

Given a fraction  $\frac{a}{b}$ , try to make it equal to  $\frac{c}{d}$  by cancelling some digits in  $a$  and  $b$

# F: Fixing Fractions

Problem Author: Michael Zündorf

## Problem

Given a fraction  $\frac{a}{b}$ , try to make it equal to  $\frac{c}{d}$  by cancelling some digits in  $a$  and  $b$

## Solution

- Try all possible  $\mathcal{O}(2^{|a|})$  subsets of  $a$
- Given  $a'$ ,  $c$  and  $d$ , we know  $b' = \frac{a' \cdot d}{c}$  must hold
- Check if  $b$  can be made into  $b'$  by removing the same digits

# F: Fixing Fractions

Problem Author: Michael Zündorf

## Problem

Given a fraction  $\frac{a}{b}$ , try to make it equal to  $\frac{c}{d}$  by cancelling some digits in  $a$  and  $b$

## Solution

- Try all possible  $\mathcal{O}(2^{|a|})$  subsets of  $a$
- Given  $a'$ ,  $c$  and  $d$ , we know  $b' = \frac{a' \cdot d}{c}$  must hold
- Check if  $b$  can be made into  $b'$  by removing the same digits

## Pitfalls

- $a' \cdot d$  not divisible by  $c$
- Leading zeroes
- 64-bit integer overflow: take GCD first, do operations modulo some prime, use bigger integers

# F: Fixing Fractions

Problem Author: Michael Zündorf

## Problem

Given a fraction  $\frac{a}{b}$ , try to make it equal to  $\frac{c}{d}$  by cancelling some digits in  $a$  and  $b$

## Solution

- Try all possible  $\mathcal{O}(2^{|a|})$  subsets of  $a$
- Given  $a'$ ,  $c$  and  $d$ , we know  $b' = \frac{a' \cdot d}{c}$  must hold
- Check if  $b$  can be made into  $b'$  by removing the same digits

## Pitfalls

- $a' \cdot d$  not divisible by  $c$
- Leading zeroes
- 64-bit integer overflow: take GCD first, do operations modulo some prime, use bigger integers


Statistics: ... submissions, ... accepted, ... unknown

# G: Galaxy Quest

Problem Author: Mike de Vries

## Problem

You are given a graph consisting of line segments in 3D space. You travel on a ship with constant acceleration and constant fuel consumption for the time spent accelerating. You need to come to a standstill at each vertex. Given a target location and a time limit, find the minimum amount of fuel needed to get there. You need to answer multiple queries, all from the same starting location.



# G: Galaxy Quest

Problem Author: Mike de Vries

## Solution for fixed path

- Consider a path consisting of multiple line segments.

# G: Galaxy Quest

Problem Author: Mike de Vries

## Solution for fixed path

- Consider a path consisting of multiple line segments.
- Suppose the  $i$ -th segment is  $d_i$  metres long and we accelerate/decelerate for  $x_i$  seconds along it.
- Then it takes  $x_i + \frac{d_i}{x_i}$  seconds to traverse the  $i$ -th segment.
- New problem: minimize  $\sum 2x_i$  subject to  $\sum x_i + \frac{d_i}{x_i} \leq t$ .
- **Key insight:** optimum is reached when  $x_i = c \cdot \sqrt{d_i}$  for some constant  $c$ .
- We can compute  $c$  by solving  $c + \frac{1}{c} = t / \sum \sqrt{d_i}$ . When the RHS is  $< 2$ , no solution exists.

## Solution

- To keep the time limit and save fuel, find a path that minimizes  $\sum \sqrt{d_i}$ .

# G: Galaxy Quest

Problem Author: Mike de Vries

## Solution for fixed path

- Consider a path consisting of multiple line segments.
- Suppose the  $i$ -th segment is  $d_i$  metres long and we accelerate/decelerate for  $x_i$  seconds along it.
- Then it takes  $x_i + \frac{d_i}{x_i}$  seconds to traverse the  $i$ -th segment.
- New problem: minimize  $\sum 2x_i$  subject to  $\sum x_i + \frac{d_i}{x_i} \leq t$ .
- **Key insight:** optimum is reached when  $x_i = c \cdot \sqrt{d_i}$  for some constant  $c$ .
- We can compute  $c$  by solving  $c + \frac{1}{c} = t / \sum \sqrt{d_i}$ . When the RHS is  $< 2$ , no solution exists.

## Solution

- To keep the time limit and save fuel, find a path that minimizes  $\sum \sqrt{d_i}$ .
- Use Dijkstra's algorithm for this, where edges have length  $\sqrt{d_i}$ .

# G: Galaxy Quest

Problem Author: Mike de Vries

## Solution for fixed path

- Consider a path consisting of multiple line segments.
- Suppose the  $i$ -th segment is  $d_i$  metres long and we accelerate/decelerate for  $x_i$  seconds along it.
- Then it takes  $x_i + \frac{d_i}{x_i}$  seconds to traverse the  $i$ -th segment.
- New problem: minimize  $\sum 2x_i$  subject to  $\sum x_i + \frac{d_i}{x_i} \leq t$ .
- **Key insight:** optimum is reached when  $x_i = c \cdot \sqrt{d_i}$  for some constant  $c$ .
- We can compute  $c$  by solving  $c + \frac{1}{c} = t / \sum \sqrt{d_i}$ . When the RHS is  $< 2$ , no solution exists.

## Solution

- To keep the time limit and save fuel, find a path that minimizes  $\sum \sqrt{d_i}$ .
- Use Dijkstra's algorithm for this, where edges have length  $\sqrt{d_i}$ .
- The starting location is fixed, so queries can be answered in constant time.

# G: Galaxy Quest

Problem Author: Mike de Vries

## Solution for fixed path

- Consider a path consisting of multiple line segments.
- Suppose the  $i$ -th segment is  $d_i$  metres long and we accelerate/decelerate for  $x_i$  seconds along it.
- Then it takes  $x_i + \frac{d_i}{x_i}$  seconds to traverse the  $i$ -th segment.
- New problem: minimize  $\sum 2x_i$  subject to  $\sum x_i + \frac{d_i}{x_i} \leq t$ .
- **Key insight:** optimum is reached when  $x_i = c \cdot \sqrt{d_i}$  for some constant  $c$ .
- We can compute  $c$  by solving  $c + \frac{1}{c} = t / \sum \sqrt{d_i}$ . When the RHS is  $< 2$ , no solution exists.

## Solution

- To keep the time limit and save fuel, find a path that minimizes  $\sum \sqrt{d_i}$ .
- Use Dijkstra's algorithm for this, where edges have length  $\sqrt{d_i}$ .
- The starting location is fixed, so queries can be answered in constant time.

Statistics: ... submissions, ... accepted, ... unknown

# H: Higher Arithmetic

Problem Author: Paul Wild

## Problem

Print a valid arithmetic expression using  $+$ ,  $\cdot$ ,  $($ , and  $)$  and all given numbers exactly once such that the value is maximal.

# H: Higher Arithmetic

Problem Author: Paul Wild

## Problem

Print a valid arithmetic expression using  $+$ ,  $\cdot$ ,  $($ , and  $)$  and all given numbers exactly once such that the value is maximal.

## Solution

- Idea: A maximal expression always is the product of sums.

# H: Higher Arithmetic

Problem Author: Paul Wild

## Problem

Print a valid arithmetic expression using  $+$ ,  $\cdot$ ,  $($ , and  $)$  and all given numbers exactly once such that the value is maximal.

## Solution

- Idea: A maximal expression always is the product of sums.
- All numbers are  $> 1$ : Multiply all numbers.

# H: Higher Arithmetic

Problem Author: Paul Wild

## Problem

Print a valid arithmetic expression using  $+$ ,  $\cdot$ ,  $($ , and  $)$  and all given numbers exactly once such that the value is maximal.

## Solution

- Idea: A maximal expression always is the product of sums.
- All numbers are  $> 1$ : Multiply all numbers.
- With 1s and 2s, some numbers need to be combined into sums.

# H: Higher Arithmetic

Problem Author: Paul Wild

## Problem

Print a valid arithmetic expression using  $+$ ,  $\cdot$ ,  $($ , and  $)$  and all given numbers exactly once such that the value is maximal.

## Solution

- Idea: A maximal expression always is the product of sums.
- All numbers are  $> 1$ : Multiply all numbers.
- With 1s and 2s, some numbers need to be combined into sums.

Cases:

# H: Higher Arithmetic

Problem Author: Paul Wild

## Problem

Print a valid arithmetic expression using  $+$ ,  $\cdot$ ,  $($ , and  $)$  and all given numbers exactly once such that the value is maximal.

## Solution

- Idea: A maximal expression always is the product of sums.
- All numbers are  $> 1$ : Multiply all numbers.
- With 1s and 2s, some numbers need to be combined into sums.

### Cases:

- Only one 1: Add to second smallest number.

# H: Higher Arithmetic

Problem Author: Paul Wild

## Problem

Print a valid arithmetic expression using  $+$ ,  $\cdot$ ,  $($ , and  $)$  and all given numbers exactly once such that the value is maximal.

## Solution

- Idea: A maximal expression always is the product of sums.
- All numbers are  $> 1$ : Multiply all numbers.
- With 1s and 2s, some numbers need to be combined into sums.

### Cases:

- Only one 1: Add to second smallest number.
- No 2s: Repeatedly combine three 1s.

# H: Higher Arithmetic

Problem Author: Paul Wild

## Problem

Print a valid arithmetic expression using  $+$ ,  $\cdot$ ,  $($ , and  $)$  and all given numbers exactly once such that the value is maximal.

## Solution

- Idea: A maximal expression always is the product of sums.
- All numbers are  $> 1$ : Multiply all numbers.
- With 1s and 2s, some numbers need to be combined into sums.

### Cases:

- Only one 1: Add to second smallest number.
- No 2s: Repeatedly combine three 1s.
  - Special case: If two 1s or four 1s, combine two 1s.

# H: Higher Arithmetic

Problem Author: Paul Wild

## Problem

Print a valid arithmetic expression using  $+$ ,  $\cdot$ ,  $($ , and  $)$  and all given numbers exactly once such that the value is maximal.

## Solution

- Idea: A maximal expression always is the product of sums.
- All numbers are  $> 1$ : Multiply all numbers.
- With 1s and 2s, some numbers need to be combined into sums.

### Cases:

- Only one 1: Add to second smallest number.
- No 2s: Repeatedly combine three 1s.
  - Special case: If two 1s or four 1s, combine two 1s.
- At least one 1 and one 2: Repeatedly combine one 1 and one 2.

# H: Higher Arithmetic

Problem Author: Paul Wild

## Problem

Print a valid arithmetic expression using  $+$ ,  $\cdot$ ,  $($ , and  $)$  and all given numbers exactly once such that the value is maximal.

## Solution

- Idea: A maximal expression always is the product of sums.
- All numbers are  $> 1$ : Multiply all numbers.
- With 1s and 2s, some numbers need to be combined into sums.

### Cases:

- Only one 1: Add to second smallest number.
- No 2s: Repeatedly combine three 1s.
  - Special case: If two 1s or four 1s, combine two 1s.
- At least one 1 and one 2: Repeatedly combine one 1 and one 2.
  - Special case: If two 1s and one 2, combine those.

# H: Higher Arithmetic

Problem Author: Paul Wild

## Problem

Print a valid arithmetic expression using  $+$ ,  $\cdot$ ,  $($ , and  $)$  and all given numbers exactly once such that the value is maximal.

## Solution

- Idea: A maximal expression always is the product of sums.
- All numbers are  $> 1$ : Multiply all numbers.
- With 1s and 2s, some numbers need to be combined into sums.

## Cases:

- Only one 1: Add to second smallest number.
- No 2s: Repeatedly combine three 1s.
  - Special case: If two 1s or four 1s, combine two 1s.
- At least one 1 and one 2: Repeatedly combine one 1 and one 2.
  - Special case: If two 1s and one 2, combine those.

Statistics: ... submissions, ... accepted, ... unknown

# I: Isolated Island

Problem Author: Michael Züendorf

## Problem

Given  $n \leq 1000$  line segments that partition the plane in small regions. Are there two regions the same *distance* from the ocean?

# I: Isolated Island

Problem Author: Michael Zündorf

## Problem

Given  $n \leq 1000$  line segments that partition the plane in small regions. Are there two regions the same *distance* from the ocean?

## Geometry solution

Find all intersections and construct the dual graph on faces:

Costs  $\mathcal{O}(n^2 \log n)$  and your sanity (256 lines of C++).

# I: Isolated Island

Problem Author: Michael Zündorf

## Problem

Given  $n \leq 1000$  line segments that partition the plane in small regions. Are there two regions the same *distance* from the ocean?

## Geometry solution

Find all intersections and construct the dual graph on faces:

Costs  $\mathcal{O}(n^2 \log n)$  and your sanity (256 lines of C++).

## Intended solution

- The difference between adjacent distances is at most 1.
- We can work modulo 2 instead.
- The answer is no iff all pairs of adjacent faces have opposite values.
- I.e.: the dual graph must be bipartite.
- That's true iff in each intersection point an even number of lines meet.
- TODO
- Solution: check if each segment endpoint appears an even number of times in the input.

# I: Isolated Island

Problem Author: Michael Zündorf

## Problem

Given  $n \leq 1000$  line segments that partition the plane in small regions. Are there two regions the same *distance* from the ocean?

## Geometry solution

Find all intersections and construct the dual graph on faces:

Costs  $\mathcal{O}(n^2 \log n)$  and your sanity (256 lines of C++).

## Intended solution

- The difference between adjacent distances is at most 1.
- We can work modulo 2 instead.
- The answer is no iff all pairs of adjacent faces have opposite values.
- I.e.: the dual graph must be bipartite.
- That's true iff in each intersection point an even number of lines meet.
- TODO
- Solution: check if each segment endpoint appears an even number of times in the input.

# J: Jogging Tour

Problem Author: Paul Wild

## Problem

Find the optimal grid angle to make a tour through  $n \leq 12$  points.

# J: Jogging Tour

Problem Author: Paul Wild

## Problem

Find the optimal grid angle to make a tour through  $n \leq 12$  points.

## Subtask: assume we know the angle

- All possible  $\mathcal{O}(n!)$  routes, too slow!
- DP with (current location, locations still todo)
- This runs in  $\mathcal{O}(n^2 \cdot 2^n)$

# J: Jogging Tour

Problem Author: Paul Wild

## Problem

Find the optimal grid angle to make a tour through  $n \leq 12$  points.

## Subtask: assume we know the angle

- All possible  $\mathcal{O}(n!)$  routes, too slow!
- DP with (current location, locations still todo)
- This runs in  $\mathcal{O}(n^2 \cdot 2^n)$

## Complete solution

- Insight: in the optimal solution, there is a straight line between two consecutive locations
- Consider all  $n^2$  angles between pairs of locations
- Total complexity  $\mathcal{O}(n^4 \cdot 2^n)$

# J: Jogging Tour

Problem Author: Paul Wild

## Problem

Find the optimal grid angle to make a tour through  $n \leq 12$  points.

## Subtask: assume we know the angle

- All possible  $\mathcal{O}(n!)$  routes, too slow!
- DP with (current location, locations still todo)
- This runs in  $\mathcal{O}(n^2 \cdot 2^n)$





## Complete solution

- Insight: in the optimal solution, there is a straight line between two consecutive locations
- Consider all  $n^2$  angles between pairs of locations
- Total complexity  $\mathcal{O}(n^4 \cdot 2^n)$

Statistics: ... submissions, ... accepted, ... unknown

# J: Jogging Tour

Problem Author: Paul Wild



# K: Klompdans

Problem Author: Maarten Sijm

## Problem

Find all reachable squares on an  $n \times n$  grid that can be reached starting from the corner while alternating between knight moves of type  $(a, b)$  and  $(c, d)$ .

# K: Klompendans

Problem Author: Maarten Sijm

## Problem

Find all reachable squares on an  $n \times n$  grid that can be reached starting from the corner while alternating between knight moves of type  $(a, b)$  and  $(c, d)$ .

## Solution

- Create two copies of the grid, one for “the last move was of type  $(a, b)$ ” and one for “the last move was of type  $(c, d)$ ”.
- Starting from the two top left corners, run BFS or DFS to find the reachable states. After each move, transfer over to the other grid.
- Count all cells that are reachable in at least one of the grids.
- Total time:  $\mathcal{O}(n^2)$ .

# K: Klompdansen

Problem Author: Maarten Sijm

## Problem

Find all reachable squares on an  $n \times n$  grid that can be reached starting from the corner while alternating between knight moves of type  $(a, b)$  and  $(c, d)$ .


## Solution

- Create two copies of the grid, one for “the last move was of type  $(a, b)$ ” and one for “the last move was of type  $(c, d)$ ”.
- Starting from the two top left corners, run BFS or DFS to find the reachable states. After each move, transfer over to the other grid.
- Count all cells that are reachable in at least one of the grids.
- Total time:  $\mathcal{O}(n^2)$ .

Statistics: ... submissions, ... accepted, ... unknown


# K: Klompendans

Problem Author: Maarten Sijm





# K: Klompendans

Problem Author: Maarten Sijm



# K: Klompendans

Problem Author: Maarten Sijm



# L: Lateral Damage

Problem Author: Paul Wild

## Problem

Play *Battleships* with a  $100 \times 100$  grid where you need to sink up to 10 aircraft carriers in at most 2500 shots, and your opponent is potentially cheating (adaptive).

# L: Lateral Damage

Problem Author: Paul Wild

## Problem

Play *Battleships* with a  $100 \times 100$  grid where you need to sink up to 10 aircraft carriers in at most 2500 shots, and your opponent is potentially cheating (adaptive).

## Observation

Shooting every fifth position in a straight line prevents your opponent from placing ships in between them.

# L: Lateral Damage

Problem Author: Paul Wild

## Problem

Play *Battleships* with a  $100 \times 100$  grid where you need to sink up to 10 aircraft carriers in at most 2500 shots, and your opponent is potentially cheating (adaptive).

## Observation

Shooting every fifth position in a straight line prevents your opponent from placing ships in between them.

## Solution

- Generalizing this observation over two dimensions:  
shoot every position on every fifth diagonal line.
- For every hit, shoot the four positions left, right, above, and below to sink the full ship.

# L: Lateral Damage

Problem Author: Paul Wild

## Problem

Play *Battleships* with a  $100 \times 100$  grid where you need to sink up to 10 aircraft carriers in at most 2500 shots, and your opponent is potentially cheating (adaptive).

## Observation

Shooting every fifth position in a straight line prevents your opponent from placing ships in between them.

## Solution

- Generalizing this observation over two dimensions:  
shoot every position on every fifth diagonal line.
- For every hit, shoot the four positions left, right, above, and below to sink the full ship.

Statistics: ... submissions, ... accepted, ... unknown

### Jury work

- 677 commits (including test session) (last year: 720)

### Jury work

- 677 commits (including test session) (last year: 720)
- 1070 secret test cases (last year: 1424) ( $89\frac{1}{6}$  per problem!)

## Random facts

### Jury work

- 677 commits (including test session) (last year: 720)
- 1070 secret test cases (last year: 1424) ( $89\frac{1}{6}$  per problem!)
- 280 jury solutions (last year: 239)

### Jury work

- 677 commits (including test session) (last year: 720)
- 1070 secret test cases (last year: 1424) ( $89\frac{1}{6}$  per problem!)
- 280 jury solutions (last year: 239)
- The minimum<sup>1</sup> number of lines the jury needed to solve all problems is

$$19 + 1 + 6 + 6 + 14 + 22 + 3 + 6 + 2 + 31 + 8 + 45 = 163$$

On average 13.6 lines per problem, down from 35.5 last year

---

<sup>1</sup>After code golfing

### Jury work

- 677 commits (including test session) (last year: 720)
- 1070 secret test cases (last year: 1424) ( $89\frac{1}{6}$  per problem!)
- 280 jury solutions (last year: 239)
- The minimum<sup>1</sup> number of lines the jury needed to solve all problems is

$$19 + 1 + 6 + 6 + 14 + 22 + 3 + 6 + 2 + 31 + 8 + 45 = 163$$

On average 13.6 lines per problem, down from 35.5 last year

- Only team ORTEC beat us: they have a submission of 22 lines for Justice Served!

---

<sup>1</sup>After code golfing

## Random facts

### Jury dedication

- Most test cases for Faster Than Light were generated after midnight and/or yesterday.

## Random facts

### Jury dedication

- Most test cases for Faster Than Light were generated after midnight and/or yesterday.
- The 80–20 rule is a thing: 80% of our time is spent on 20% of the problem statement.

## Random facts

### Jury dedication

- Most test cases for Faster Than Light were generated after midnight and/or yesterday.
- The 80–20 rule is a thing: 80% of our time is spent on 20% of the problem statement.
- The longest discussions were about tiny style issues like “illustration” vs. “visualisation”.

